NaWoo

Technical Data Sheet · NW-C series

Issued 04 Nov 2026

WPC Composite Decking Tiles 300 × 300 mm

Wood-plastic composite boards on an interlocking base. Grooved, slip-resistant surface that does not splinter or need oiling. Ideal around pools and in high-traffic areas.

Specifications

Size	300 × 300 mm
Thickness	[XX] mm
Composition	[XX]% wood fibre, [XX]% HDPE
Surface	Grooved [/ wood-grain embossed]
Weight per tile	[X.X] kg
Tiles per box	[XX] pcs
Loading 20' / 40' HC	[XXXX] / [XXXX] boxes
HS code	[3925.xx]
Lead time	[XX] days

Packaging & container loading

Item	Tiles / box	m² / box	Carton L×W×H (cm)	Net / gross (kg)	Boxes / pallet	40' HQ load	m² / 40' HQ
[WPC code] 300 × 300 × [XX] mm	[ ]	[ ]	[ ]	[ ] / [ ]	[ ]	[ ] pallets · [ ] boxes loose: [ ] boxes	[ ]

Warranty

[X] years. Covers: Cracking, splitting and abnormal fading.

NaWoo · Phuc Le Village, Ke Sat Commune, Hai Phong City, Vietnam · heroduc@nawoo.vn · +84 914 266 969 · nawoo.vn

Figures marked [ ] are being confirmed. Specifications may change; confirm with your order.